

Technique

Semi-permanent sealer



Technique is a stain resistant floor sealer for use on all internal resilient floors such as vinyl and porous composite tiles. Technique is a semi permanent sealer that enhances the appearance of old floors when used with a Diversey finish according to directions.

Features:

- ▶ Semi-permanent sealer ideal for use as a base coat
- ▶ Can be used on all internal resilient floors such as vinyl and porous composite tiles as well as vinyl asbestos tiles
- ▶ Seals and protects against stains
- ▶ Technique enhances the appearance of old and worn out floors
- ▶ Provides protection to floor against a wide variety of damaging and staining substances

Benefits:

- ▶ Very resistant to common floor spills
- ▶ Provides greater protection to floor

Designed For

- ▶ Retail
 - ▶ Education
 - ▶ Government
 - ▶ Healthcare
 - ▶ Institutional Facilities
-

Use Overview

Instructions for Use:

Application

1. Strip old coatings using a Diversey stripper according to label directions. Allow floor to dry
2. Apply 2-3 coats of Technique using a clean mop or applicator.
3. Allow coat to dry for 20-30 minutes depending on drying conditions.
4. Apply 2-4 further coats of Diversey finish as required staying 10-20 cm from the edges on each second coat.

Removal

1. Use Diversey stripper diluted according to label directions with a 7-10 minute contact time. Rewet with additional stripper solution.
2. Scrub thoroughly with a brush or aggressive pad. If coats are heavy, a second strip may be required.
3. Re-apply coats of Technique using a clean mop or applicator.
4. Apply 2-4 further coats of Diversey finish as required staying 10-20 cm from the edges on each second coat.

Top Coat Removal – Unbuffered Floors

1. Remove Diversey top coat finish with blue pad and Diversey stripper according to label directions. Allow floor to dry.
2. Apply 2-4 further coats of Diversey finish as required staying 10-20 cm from the edges on each second coat.
3. Allow coats to dry for 20-30 minutes depending on drying conditions.
4. Maintain the Diversey finish gloss using periodic recoating, spray buffing or burnishing according to finish label directions.
5. Wash out all equipment before storage.

Technical data

Description	
Appearance	Opaque white liquid
Odour	Characteristic odour
pH (concentrate)	8.3 – 8.8
Specific Gravity	1.03
Coverage	30 – 40m ² per liter
Drying time	30-45mins
Slip classification	Class F (AS/NZS 4586:1999)

Available Items

Code	Description	Pack Size	Dilution	Availability
5687622	Technique	2x5L	Neat	AU & NZ

These figures are typical values and should not be interpreted as specifications.

Safe handling and storage information:

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity.

Product compatibility:

Under recommended conditions of use, Technique is suitable on all internal resilient floors such as vinyl, rubber and porous composite tiles.

Safety Reminder:

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:

Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615
www.diversey.com